

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Concrete Film Remover**

Article number: 10810, 10811, 10866

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Cleaning agent/ Cleaner

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

STOT SE 3 H335 May cause respiratory irritation.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Storage:

Store locked up.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS05 GHS07

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

Trade name: Concrete Film Remover

(Contd. of page 1)

<ul style="list-style-type: none"> · <u>Signal word</u> · <u>Hazard-determining components of labelling:</u> · <u>Hazard statements</u> · <u>Precautionary statements</u> 	<p>Danger</p> <p>phosphoric acid hydrogen chloride Aliphatic alcohols, C13-C15, largely linear, ethoxylated</p> <p>H314 Causes severe skin burns and eye damage. H335 May cause respiratory irritation.</p> <p>P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P280 Wear protective gloves/protective clothing/eye protection/face protection. P260 Do not breathe mist/vapours/spray. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p>
<ul style="list-style-type: none"> · 2.3 Other hazards · <u>Results of PBT and vPvB assessment</u> · <u>PBT:</u> · <u>vPvB:</u> 	<p>Not applicable. Not applicable.</p>

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

	non-ionic surfactants ☠ Eye Dam. 1, H318 ☠ Acute Tox. 4, H302	1-5%
CAS: 7664-38-2 EINECS: 231-633-2 Index number: 015-011-00-6 Reg.nr.: 01-2119485924-24	phosphoric acid ☠ Met. Corr.1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318	12.5-25%
CAS: 7647-01-0 EINECS: 231-595-7 Index number: 017-002-01-X	hydrogen chloride ☠ Skin Corr. 1B, H314 ☠ STOT SE 3, H335	12.5-25%
CAS: 25749-64-8 Reg.nr.: 01-2120065599-40-0000	2-Propyn-1-ol, ethoxyliert ☠ Acute Tox. 2, H330 ☠ Eye Dam. 1, H318 ☠ Acute Tox. 4, H302; STOT SE 3, H335	<1%

· Regulation (EC) No 648/2004 on detergents / Labelling for contents

non-ionic surfactants	< 5%
-----------------------	------

· Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

Trade name: Concrete Film Remover

(Contd. of page 2)

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Cramp
Gastric or intestinal disorders
Nausea

Information for doctor:

Symptoms in intoxication with acids:
In case of oral intake symptoms depend on concentration and acidity of incorporated acid, and are corrosive eschar in mouth and throat, vomiting, severe dysphagia, shock and coma. Therapy measures: drink plenty of water. Administer 20 g Magnesia usta in milk oral; no hydrogen carbonate oral; pain relief measures; in indication of acidosis infusion of sodium hydrogencarbonate solution(5%).

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Hydrogen chloride (HCl)

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained respiratory protective device.
Wear fully protective suit.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Particular danger of slipping on leaked/spilled product.
Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

Trade name: Concrete Film Remover

(Contd. of page 3)

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

No special measures required.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

No special requirements.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Protect from frost.
Keep container tightly sealed.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection**Additional information about design of technical facilities:**

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****7664-38-2 phosphoric acid**

WEL	Short-term value: 2 mg/m ³ Long-term value: 1 mg/m ³
-----	---

DNELs**7664-38-2 phosphoric acid**

Inhalative	DNEL (Langzeit-wiederholt)	2.92 mg/m ³ Air (ARB) 0.73 mg/m ³ Air (BEV)
------------	----------------------------	--

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Clean skin thoroughly immediately after handling the product.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: Preventive skin protection by use of skin-protecting agents is recommended. After use of gloves apply skin-cleaning agents and skin cosmetics. Skin protection agent recommendation for preventive skin shelter without use of protective gloves:
STOKODERM (<http://www.stoko.com>)
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
STOKO EMULSION (<http://www.stoko.com>)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

Trade name: Concrete Film Remover

(Contd. of page 4)

Skin protection recommendation for skin cleaning after product handling:

FRAPANTOL (<http://www.stoko.com>)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (<http://www.stoko.com>)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR
 Fluorocarbon rubber (Viton)
 Nitrile rubber, NBR
 Chloroprene rubber, CR
 Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level \leq 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR
 Butoject (KCL, Art_No. 897, 898)
 Fluorocarbon rubber (Viton)
 Vitoject (KCL, Art_No. 890)
 Nitrile rubber, NBR
 Camatril (KCL, Art_No. 730, 731, 732, 733)
 Chloroprene rubber, CR
 Camapren (KCL, Art_No. 720, 722, 726)
 Neoprene gloves

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR
 Camatril (KCL, 730, 731, 732, 733)
 Chloroprene rubber, CR
 Camapren (KCL, Art_No. 720, 722, 726)
 Nitopren (KCL, Art_No. 717)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

Trade name: Concrete Film Remover

(Contd. of page 5)

· Not suitable are gloves made of the following materials:

Leather gloves
Strong material gloves

· Eye protection:



Tightly sealed goggles

· Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: Yellow-brown

· Odour: Pungent

· pH-value at 20 °C: < 1

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 85 °C

· Flash point: Not applicable.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Vapour pressure at 20 °C: 23 hPa

· Density at 20 °C: 1.14 g/cm³

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Viscosity:

Dynamic: Not determined.
Kinematic at 20 °C: 11 s (DIN 53211/4)

· Solvent content:

Organic solvents: 0.0 %
Water: 69.2 %

· Solids content: 20.6 %

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· **10.3 Possibility of hazardous reactions**

Reacts with strong oxidising agents.
Reacts with metals forming hydrogen.

· **10.4 Conditions to avoid**

No further relevant information available.

· **10.5 Incompatible materials:**

No further relevant information available.

· **10.6 Hazardous decomposition products:**

Hydrogen chloride (HCl)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

Trade name: Concrete Film Remover

(Contd. of page 6)

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	63 mg/l
------------	----------	---------

7664-38-2 phosphoric acid

Oral	LD50	2600 mg/kg (rat)
Dermal	LD50	2740 mg/kg (rabbit)
Inhalative	LC50/1h	1.69 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**

· Aquatic toxicity:

7664-38-2 phosphoric acid

EC50	270 mg/l (BES)
	270 mg/l (bacteria)
EC50/48h	>100 mg/l (daphnia magna)
EC50/72h	>100 mg/l (Desmodesmus subspicatus)
LC50/96h	138 mg/l (Gambusia affinis)
	98-106 mg/l (lem)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

Trade name: Concrete Film Remover

· **12.6 Other adverse effects** No further relevant information available.

(Contd. of page 7)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 29*	detergents containing hazardous substances

· Uncleaned packaging:

· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA UN3264

· 14.2 UN proper shipping name

· ADR 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID)

· IMDG, IATA CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID)

· 14.3 Transport hazard class(es)

· ADR



· Class 8 (C1) Corrosive substances.

· Label 8

· IMDG, IATA



· Class 8 Corrosive substances.

· Label 8

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

· Danger code (Kemler): Warning: Corrosive substances.
80

· EMS Number: F-A,S-B

· Segregation groups Acids

· Stowage Category A

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

Trade name: Concrete Film Remover

(Contd. of page 8)

· <u>Stowage Code</u>	SW2 Clear of living quarters.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· <u>Transport/Additional information:</u>	
· <u>ADR</u>	
· <u>Limited quantities (LQ)</u>	5L
· <u>Excepted quantities (EQ)</u>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>Transport category</u>	2
· <u>Tunnel restriction code</u>	E
· <u>IMDG</u>	
· <u>Limited quantities (LQ)</u>	5L
· <u>Excepted quantities (EQ)</u>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>UN "Model Regulation":</u>	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID), 8, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I hydrogen chloride
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H290 May be corrosive to metals.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H335 May cause respiratory irritation.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Dieter Zimmermann
Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2016

Version number 3

Revision: 28.10.2016

Trade name: Concrete Film Remover

(Contd. of page 9)

ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Met. Corr. 1: Corrosive to metals – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB